

Material Safety Data Sheet

Status: 08/23/2012

Version: 1.0



ACRYLITE® Resist - Sheet/Tube

Page 1 of 7

1. Chemical Product and Company Identification

ACRYLITE® Resist - Sheet/Tube

Supplier:

Evonik CYRO LLC
299 Jefferson Road
Parsippany, NJ 07054-0677
+1-973-929-8000

Product Information Number 1-207-490-4242
24 Hour Emergency Number, CHEMTREC 1-800-424-9300

Product Use: building glazing, light advertising, furniture, trade-fair booth design, displays, decoration, Industrial use

2. Composition/Information on Ingredients

This material is classified as not hazardous under OSHA regulations.

<u>Ingredients</u>	<u>CAS Reg. No.</u>	<u>Weight %</u>
acrylic copolymer		trade secret

NJTSR # 56705700001-7127P

See Section 8, Exposure Controls/Personal Protection

3. Hazards Identification

Emergency Overview

Color: transparent
Appearance: sheets
Odor: odourless

Under normal conditions of use, this product is not expected to create any unusual industrial hazards.

Primary Routes of Exposure

Eye contact (if exposed to chips)

Potential Health Effects

Inhalation

No hazard expected in normal use.

Eye Contact

No hazard expected in normal use.

Material can cause the following:
- mechanical irritation

Material Safety Data Sheet

Status: 08/23/2012

Version: 1.0



ACRYLITE® Resist - Sheet/Tube

Page 2 of 7

Skin Contact

Material can cause the following:
- cuts (when using cut sheets)

Ingestion

No hazard expected in normal use.

Potential Environmental Effects

See SECTION 12, Ecological Information

4. First Aid Measures

First Aid Procedures

Inhalation

No specific treatment is necessary since this material is not likely to be hazardous by inhalation.

Eye Contact

If mechanical irritation occurs flush eyes thoroughly with a large amount of water, consult a physician if irritation persists. (possible during machining processes)

Skin Contact

No specific treatment is necessary since this material is not likely to be hazardous.

Ingestion

Ingestion is not considered a potential route of exposure.

Note to Physician

None known
no

5. Fire-Fighting Measures

Flash point > 250 °C (ASTM D 1929-68)
> 480 °F (ASTM D 1929-68)

Ignition temperature > 400 °C (ASTM D 1929-68)
> 750 °F (ASTM D 1929-68)

Lower explosion limit not applicable

Upper explosion limit not applicable

OSHA Flammability Classification none

Other Flammable Properties

Use water spray to cool containers exposed to fire.

Unusual Hazards

In case of fire partly flammable, partly harmful vapours, which are irritating to the eyes and respiratory system, may be formed on thermal decomposition. -

Extinguishing Media

Use the following extinguishing media when fighting fires involving this material:
water spray - foam - dry chemical - carbon dioxide

Fire Fighting Procedures

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Material Safety Data Sheet

Status: 08/23/2012

Version: 1.0



ACRYLITE® Resist - Sheet/Tube

Page 3 of 7

6. Accidental Release Measures

Procedures

Collect material and place in a disposal container. Obey relevant local, state, provincial and federal laws and regulations.

Should not be released into the environment. Collect and dispose of unused residues.

See Material Safety Data Sheet section 8, Exposure Controls/Personal Protection.

7. Handling and Storage

Handling

Avoid dust formation. During thermoplastic processing, vapours of the decomposition products referred to in section 10 are given off, which are technically unavoidable (Observe exposure threshold limit values). During thermal processing and/or machining local exhaust ventilation at processing machines is necessary.

Storage

Storage: dry.

8. Exposure Controls/Personal Protection

Exposure Limit Information

ACRYLIC COPOLYMER

trade secret

No Occupational Exposure Values established (ACGIH, OSHA, Canada and Mexico).

Engineering Controls (Ventilation)

If use operations generate dust, use adequate ventilation.

Respiratory Protection

A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

Eye Protection

goggles for machining operations

Hand Protection

protective gloves against mechanical risks

Other Protective Equipment

To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132) be conducted before using this product.

9. Physical and Chemical Properties

Appearance transparent

Physical state sheets

Material Safety Data Sheet

Status: 08/23/2012

Version: 1.0



ACRYLITE® Resist - Sheet/Tube

Page 4 of 7

Odor	odourless
Flash point	> 250 °C (ASTM D 1929-68) > 480 °F (ASTM D 1929-68)
pH-value	not applicable
Viscosity (dynamic)	not applicable
Specific gravity (water = 1)	approx. 1.20 g/cm ³ at 20 °C / 68 °F
Vapor density (air = 1)	not applicable
Vapor pressure	not applicable
Softening Temperature	approx. approx. 100 °C / 210 °F
Boiling Temperature	not applicable
Solubility in water	insoluble
Bulk density	not available
Solubility (qualitative)	in e.g. esters, ketones and chlorinated hydrocarbons: readily soluble
n-Octanol/water partition coefficient	not applicable
Evaporation rate	not applicable
Odor threshold	not available
Further information	none

See Section 5, Fire Fighting Measures

10. Stability and Reactivity

Stability

This material is considered stable under specified conditions of storage, shipment and/or use.

Conditions To Avoid

High temperature. Depolymerization begins at 250 °C / 482 °F.

Incompatibility With Other Materials

None reasonably foreseeable.

Hazardous Decomposition Products

No hazardous decomposition products known.

Hazardous Polymerization

No hazardous reactions known.

11. Toxicological Information

Acute Oral Toxicity

no specific test data available no evidence for hazardous properties (structure-activity-relationships) (analogy)

Irritant Effect on the Skin

no specific test data available no evidence for hazardous properties (structure-activity-relationships) (analogy)

Material Safety Data Sheet

Status: 08/23/2012

Version: 1.0



ACRYLITE® Resist - Sheet/Tube

Page 5 of 7

Irritant Effect on the Eyes

no specific test data available no evidence for hazardous properties (structure-activity-relationships) (analogy)

Sensitization

no specific test data available no evidence for hazardous properties (structure-activity-relationships) (analogy)

Mutagenicity

no specific test data available
no evidence for hazardous properties
(structure-activity-relationships)
(analogy)

Carcinogenicity

no specific test data available
no evidence for hazardous properties
(structure-activity-relationships)
(analogy)

Reprotoxicity / teratogenicity

no specific test data available
no evidence for hazardous properties
(structure-activity-relationships)
(analogy)

Further Information on Toxicology

The product has not been tested toxicologically. When handled and used as directed the product will not cause hazardous effects to health according to studies on similar products and practical experience. The fine particles contained in the product may cause mechanical irritations of the skin, eyes and mucous membranes. Avoid skin and eye contact and inhalation of product dust/aerosols.

12. Ecological Information

Information on Elimination (Persistence and Degradability)

Bioaccumulation

Ecotoxicological Effect

Further Information on Ecology

The product has not been tested ecotoxicologically.

On the basis of the products consistency as well as its low water solubility a bioavailability is unlikely. Studies on products with similar composition confirm this assumption. Prevent substance from entering soil, natural bodies of water and sewer systems.

13. Disposal Considerations

Procedures

Waste must be disposed of in accordance with federal, state and local regulations. Incineration is the preferred method. CYRO encourages the recycle, recovery and reuse of materials, where permitted, as an alternate to disposal as a waste.

Material Safety Data Sheet

Status: 08/23/2012

Version: 1.0



ACRYLITE® Resist - Sheet/Tube

Page 6 of 7

14. Transport Information

Further information

Not subject to the regulations on dangerous goods.

15. Regulatory Information

INVENTORY INFORMATION

REACH (EU)	preregistered, registered or exempted
TSCA (USA)	listed or exempted
DSL (CDN)	listed or exempted
AICS (AUS)	listed or exempted
METI (J)	listed or exempted
ECL (KOR)	listed or exempted
PICCS (RP)	listed or exempted
IECSC (CN)	listed or exempted
HSNO (NZ)	listed or exempted

US FEDERAL REGULATORY INFORMATION

Component / CASRN	TPQ [lbs]	CERCLA RQ [lbs] (40CFR302.4)	SARA 302 List of EHS	SARA 313 (40CFR372)	TSCA 12b
NONE					

COMPONENT CLASSIFICATION UNDER CLEAN AIR ACT SECTION 112

Component / CASRN	Weight %	HAP	EHAP
NONE			

PRODUCT CLASSIFICATION UNDER SECTION 311/312 OF SARA (40CFR370)

NONE

US STATE REGULATORY INFORMATION

Component / CASRN	New Jersey RTK	Pennsylvania RTK	Massachusetts RTK	California Proposition 65 Cancer	California Proposition 65 Reproductive
acrylic polymer / secret					

This product contains (a) chemical(s) known to the State of California to cause cancer.

Material Safety Data Sheet

Status: 08/23/2012

Version: 1.0



ACRYLITE® Resist - Sheet/Tube

Page 7 of 7

CANADIAN REGULATION

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation and the MSDS contains all information required by the Controlled Products Regulations.

This is a non-controlled product.

WHMIS: NO

Component / CASRN

NPRI

NONE

16. Other Information

Recommended restriction(s) for use

None known.

	Health	Flammability	Physical Hazard
HMIS-Ratings	0	1	0
NFPA-Ratings	0	1	0

HMIS Hazard Ratings	NFPA Hazard Ratings
4 = severe	4 = extreme
3 = serious	3 = high
2 = moderate	2 = moderate
1 = slight	1 = slight
0 = minimal	0 = insignificant
N = no rating for powders	N = no rating for powders
* = chronic health hazard	

This MSDS was prepared in accordance with ANSI Z400.1-1998.

Places marked by || have been amended from the last version.

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

Date of printing : 12/02/2014