Update: 07/11/2013 Version: 1.1

ACRYLITE® - Sheets/Rods/Tubes



100

Page 1 of 7

# 1. Chemical Product and Company Identification

# ACRYLITE® - Sheets/Rods/Tubes

Supplier:

**Evonik CYRO LLC** 

299 Jefferson Road Parsippany, NJ 07054-0677 +1-973-929-8000

Product Information Number 1-207-490-4242 24 Hour Emergency Number, CHEMTREC 1-800-424-9300

Product Use: building glazing, light advertising, furniture, trade-fair booth design, displays,

decoration, Industrial use

# 2. Composition/Information on Ingredients

This material is classified as not hazardous under OSHA regulations.

<u>Ingredients</u> <u>CAS Reg. No.</u> <u>Weight %</u>

trade secret

NJTSR # 56705700001-7119P

See Section 8, Exposure Controls/Personal Protection

### 3. Hazards Identification

acrylic copolymer

## **Emergency Overview**

Color: transparent Appearance: sheets Odor: odourless

Under normal conditions of use, this product is not expected to create any unusual industrial hazards.

### **Primary Routes of Exposure**

Eye contact (if exposed to chips)

### **Potential Health Effects**

### Inhalation

No hazard expected in normal use.

## **Eye Contact**

No hazard expected in normal use. Material can cause the following:

- mechanical irritation

Update: 07/11/2013 Version: 1.1



ACRYLITE® - Sheets/Rods/Tubes

Page 2 of 7

#### **Skin Contact**

Material can cause the following:
- cuts (when using cut sheets)

### Ingestion

No hazard expected in normal use.

#### **Potential Environmental Effects**

See SECTION 12, Ecological Information

### 4. First Aid Measures

### **First Aid Procedures**

### Inhalation

No specific treatment is necessary since this material is not likely to be hazardous by inhalation.

### **Eve Contact**

If mechanical irritation occurs flush eyes thoroughly with a large amount of water, consult a physician if irritation persists. (possible during machining processes)

#### **Skin Contact**

No specific treatment is necessary since this material is not likely to be hazardous.

## Ingestion

Ingestion is not considered a potential route of exposure.

### Note to Physician

None known

no

# 5. Fire-Fighting Measures

Flash point > 250 °C ( ASTM D 1929-68 )

> 480 °F (ASTM D 1929-68)

Ignition temperature > 400 °C ( ASTM D 1929-68 )

> 750 °F (ASTM D 1929-68)

Lower explosion limit not applicable

Upper explosion limit not applicable

OSHA Flammability Classification none

#### **Other Flammable Properties**

Use water spray to cool containers exposed to fire.

### **Unusual Hazards**

In case of fire partly flammable, partly harmful vapours, which are irritating to the eyes and respiratory system, may be formed on thermal decomposition. -

### **Extinguishing Media**

Use the following extinguishing media when fighting fires involving this material:

water spray - foam - dry chemical - carbon dioxide

### **Fire Fighting Procedures**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Update: 07/11/2013 Version: 1.1





Page 3 of 7

#### 6. Accidental Release Measures

### **Procedures**

Collect material and place in a disposal container. Obey relevant local, state, provincial and federal laws and regulations.

Should not be released into the environment. Collect and dispose of unused residues. See Material Safety Data Sheet section 8, Exposure Controls/Personal Protection.

## 7. Handling and Storage

### Handling

Avoid dust formation. During thermoplastic processing, vapours of the decomposition products referred to in section 10 are given off, which are technically unavoidable (Observe exposure threshold limit values). During thermal processing and/or machining local exhaust ventilation at processing machines is necessary.

### Storage

Storage: dry.

## 8. Exposure Controls/Personal Protection

### **Exposure Limit Information**

## **ACRYLIC COPOLYMER**

trade secret

No Occupational Exposure Values established (ACGIH, OSHA, Canada and Mexico).

## **Engineering Controls (Ventilation)**

If use operations generate dust, use adequate ventilation.

## **Respiratory Protection**

A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

### **Eye Protection**

goggles for machining operations

### **Hand Protection**

protective gloves against mechanical risks

## **Other Protective Equipment**

To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132) be conducted before using this product.

## 9. Physical and Chemical Properties

Appearance transparent
Physical state sheets

Update: 07/11/2013 Version: 1.1



ACRYLITE® - Sheets/Rods/Tubes

Page 4 of 7

**Odor** odourless

**Flash point** > 250 °C ( ASTM D 1929-68 )

> 480 °F (ASTM D 1929-68)

pH-value not applicable
Viscosity (dynamic) not applicable

Specific gravity (water = 1) ca. 1.20 g/cm3 at 20 °C / 68 °F

Vapor density (air = 1) not applicable
Vapor pressure not applicable

Softening Temperature ca.ca. 100 °C / 210 °F

Boiling Temperaturenot applicableSolubility in waterinsolubleBulk densitynot available

**Solubility (qualitative)** in e.g. esters, ketones and chlorinated hydrocarbons: readily

soluble

n-Octanol/water partition

coefficient

not applicable

Evaporation rate not applicable

Odor threshold not available

**Further information** none See Section 5, Fire Fighting Measures

## 10. Stability and Reactivity

### Stability

This material is considered stable under specified conditions of storage, shipment and/or use.

### **Conditions To Avoid**

High temperature. Depolymerization begins at 250 °C / 482 °F.

## **Incompatibility With Other Materials**

None reasonably foreseeable.

### **Hazardous Decomposition Products**

No hazardous decomposition products known.

## **Hazardous Polymerization**

No dangerous reactions known.

# 11. Toxicological Information

## **Acute Oral Toxicity**

no specific test data available no evidence for hazardous properties (structure-activity-relationships) (analogy)

## Irritant Effect on the Skin

no specific test data available no evidence for hazardous properties (structure-activity-relationships) (analogy)

Update: 07/11/2013 Version: 1.1

ACRYLITE® - Sheets/Rods/Tubes



Page 5 of 7

### **Irritant Effect on the Eyes**

no specific test data available no evidence for hazardous properties (structure-activity-relationships) (analogy)

#### Sensitization

no specific test data available no evidence for hazardous properties (structure-activity-relationships) (analogy)

### Mutagenicity

no specific test data available no evidence for hazardous properties (structure-activity-relationships) (analogy)

### Carcinogenicity

no specific test data available no evidence for hazardous properties (structure-activity-relationships) (analogy)

### Reprotoxicity / teratogenicity

no specific test data available no evidence for hazardous properties (structure-activity-relationships) (analogy)

### **Further Information on Toxicology**

The product has not been tested toxicologically. When handled and used as directed the product will not cause hazardous effects to health according to studies on similar products and practical experience. The fine particles contained in the product may cause mechanical irritations of the skin, eyes and mucous membranes. Avoid skin and eye contact and inhalation of product dust/aerosols.

### 12. Ecological Information

Information on Elimination (Persistence and Degradability) Bioaccumulation

## **Ecotoxicological Effect**

### **Further Information on Ecology**

The product has not been tested ecotoxicologically.

On the basis of the products consistency as well as its low water solubility a bioavailability is unlikely. Studies on products with similar composition confirm this assumption. Prevent substance from entering soil, natural bodies of water and sewer systems.

## 13. Disposal Considerations

### **Procedures**

Waste must be disposed of in accordance with federal, state and local regulations. Incineration is the preferred method. CYRO encourages the recycle, recovery and reuse of materials, where permitted, as an alternate to disposal as a waste.

Update: 07/11/2013 Version: 1.1

ACRYLITE® - Sheets/Rods/Tubes



Page 6 of 7

## 14. Transport Information

### **Further information**

Not subject to the regulations on dangerous goods.

# 15. Regulatory Information

#### **INVENTORY INFORMATION**

REACH (EU) TSCA (USA) DSL (CDN) AICS (AUS) METI (J) ECL (KOR) PICCS (RP) IECSC (CN) HSNO (NZ)	preregistered, registered or exempted listed or exempted
HSNO (NZ) ECS (Taiwan)	listed or exempted listed or exempted

## **US FEDERAL REGULATORY INFORMATION**

Component / CASRN	TPQ [lbs]	CERCLA RQ [lbs]	SARA 302	<b>SARA 313</b>	TSCA 12b
		(40CFR302.4)	List of EHS	(40CFR372)	

NONE

### **COMPONENT CLASSIFICATION UNDER CLEAN AIR ACT SECTION 112**

Component / CASRN	Weight %	HAP	EHAP

NONE

# PRODUCT CLASSIFICATION UNDER SECTION 311/312 OF SARA (40CFR370)

NONE

## **US STATE REGULATORY INFORMATION**

Component / CASRN	New Jersey RTK	Pennsylvania RTK	Massachusetts RTK	California Proposition 65 Cancer	California Proposition 65 Reproductive
acrylic polymer / secret	NO	NO	NO	NO	NO

This product contains (a) chemical(s) known to the State of California to cause cancer.

Update: 07/11/2013 Version: 1.1





Page 7 of 7

### **CANADIAN REGULATION**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation and the MSDS contains all information required by the Controlled Products Regulations.

This is a non-controlled product.

WHMIS: NO

Component / CASRN NPRI

NONE

### 16. Other Information

## Recommended restriction(s) for use

None known.

	Health	Flammability	Physical Hazard	
HMIS-Ratings	0	1	0	
NFPA-Ratings	0	1	0	
	HMIS Hazard Ratings	NFPA Ha	azard Ratings	
	4 = severe 3 = serious 2 = moderate 1 = slight 0 = minimal N = no rating for powders * = chronic health hazard	4 = extre 3 = high 2 = mode 1 = slight 0 = insign N = no re	erate	

This MSDS was prepared in accordance with ANSI Z400.1-1998.

Places marked by have been amended from the last version.

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

Date of printing: 12/02/2014