



UL Test Results

(go back to previous page)

QMFZ2.E100599 Plastics - Component

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

See [General Information for Plastics - Component](#)

Material Dsg	Color	Min. Thk mm	Flame Class	H		R T I		Mech		H V R	D 4 5	C T I
				W I	A I	Elec	Imp	Str				
Polyvinylchloride (PVC), PVC structural foam, furnished as sheets.												
Komacel 654/10	WT	10.0	V-0, 5VB	-	-	50	50	50	-	-	-	-
Komacel 654/4-6	WT	4.0-6.0	V-0	-	-	50	50	50	-	-	-	-
		6.0 - 6.6	V-0,5VA	-	-	50	50	50				
Komatex 1-6	WT	1.0	V-0, 5VB	-	-	50	50	50	-	-	-	-
	ALL	2.0	V-0, 5VB	-	-	50	50	50				
		3.0	V-0, 5VA	-	-	50	50	50				
		6.0	V-0, 5VA	-	-	50	50	50				
Komatex New (b) (c)												
	ALL	3	V-0,5VB	-	-	50	50	50	-	-	-	-
Komatex New A (d)	WT	1.0 - 1.1	V-0,5VB	-	-	50	50	50	-	-	-	-
Komatex New B (e)	WT	2.0 - 4.0	V-0,5VB	-	-	50	50	50	-	-	-	-
Komatex New C (f)	WT	5.0 - 5.5	V-0,5VB	-	-	50	50	50	-	-	-	-
Komatex New D (g)	WT	6.0 - 6.6	V-0,5VB	-	-	50	50	50	-	-	-	-
Komatex New E (h)	WT	8.0 - 10.0	V-0,5VA	-	-	50	50	50	-	-	-	-
Komatex/1-3	WH	1.0-3.0	V-0	-	-	50	50	50	-	-	-	-
Komatex/3-6	WH	1.0-3.0	V-0	-	-	50	50	50	-	-	-	-
	ALL	3.0-6.0	V-0	-	-	50	50	50				
Polyvinylchloride (PVC), structural foam w/ smooth outer skin, furnished as sheets.												
Komacel 652	WT	9.5	V-0	-	-	50	50	50	-	-	-	-
Polyvinylchloride (PVC), furnished as sheets.												
Komadur ES 1-10	ALL	0.9	V-0, 5VB	-	-	50	50	50	-	-	-	-
Komadur ES 669	WT	0.97	V-0	-	-	50	50	50	-	-	-	-
Komadur WA (a)	WT, GY	1.0	V-0	-	-	50	50	50	-	-	-	-
		6.0	V-0	-	-	50	50	50				
		12.0	V-0	-	-	50	50	50				
Komadur WA 1-30 (a)												
	NC, WT, GY	0.9	V-0, 5VB	-	-	50	50	50	-	-	-	-

- (a) - Gray color may be either light or dark gray
- (b) - for density range of 0.502 - 0.614 g/cc
- (c) - Excluding color WT
- (d) - for density range of 0.734 - 0.898 g/cc
- (e) - for density range of 0.552 - 0.674 g/cc
- (f) - for density range of 0.473 - 0.578 g/cc
- (g) - for density range of 0.503 - 0.614 g/cc
- (h) - for density range of 0.437 - 0.534 g/cc

Marking: Company name and material designation on container, wrapper or finished part.

Made in the USA



[PVC Color](#) | [KOMATEX](#) • [PVC Wood](#) | [KOMACEL Plus Embossed](#) • [PVC Printing](#) | [KOMACEL](#) • [Plastic Sheet PVC](#) | [KOMACEL Plus](#) • [Aluminum Clad](#) | [KOMAALU](#) • [Polystyrene Foam](#) | [KOMAFOAM](#) • [Polystyrene Foam](#) | [KOMAFOAM](#) • [Type 1 PVC](#) | [KOMADUR](#)

[Kömmerling International Link](#) 

© 2013 KommerlingUSA, Inc. | [800-330-2239](#) | [256-851-4099](#) | [sitemap](#)